

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Cadmium-Tin Solders for Most Metals

SDS Number: 151

Page 1 of 4

SECTION I: PRODUCT AND COMPANY INFORMATION

Product Name: Kapp Alloy Cadmium-Tin Solders for Most Metals
 CAS Number: Cadmium (Cd): 7440-43-9 and Tin (Sn): 7440-31-5

Company Identification: Kapp Alloy & Wire, Inc., 1 Klein Street / PO Box 1188, Oil City, PA 16301
 Contact: Telephone: 1-800-327-6533 or 814-676-0613, Fax: 814-676-5565, Email: info@kappalloy.com

SECTION II: HAZARD INFORMATION

GHS08 Health Hazard

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 – May cause cancer.

H361 – Suspected of damaging fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.



GHS07

H302 - Harmful if swallowed.



GHS09

H400 - Very toxic to aquatic life

H413 - May cause long lasting harmful effects to aquatic life.



GHS07



GHS08



GHS09

Label Elements: Hazard Pictograms

Signal Word: **Danger**

Hazard-determining components of labeling: Cadmium

Hazard Statements:

H302 - Harmful if swallowed.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 - May cause an allergic skin reaction.

H351 – May cause cancer.

H361 – Suspected of damaging fertility or the unborn child.

H373 – May cause damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H413 - May cause long lasting harmful effects to aquatic life.

Precautionary Statements:

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P234 - Keep only in original container

P260 - Do not breathe dust/fumes.

P263 - Avoid contact during pregnancy/while nursing.

P264 - Wash thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash

+P302+P352 thoroughly with soap and water to remove any residue. If a rash develops, call a physician.

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Cadmium-Tin Solders for Most Metals

SDS Number: 151

Page 2 of 4

P305+P351+P338 – IF IN EYES: Flush with water for at least 15 minutes to remove irritant. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician.

P304+P341 – IF INHALED: Terminate exposure and remove to fresh air. Call physician; advise of chemical composition (section III).

P308+P313 - IF exposed or concerned: Get medical advice/attention

P310 - Immediately call a POISON CENTER/doctor

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION III: COMPOSITION / INGREDIENTS

*(Hazardous components 1% or greater; Carcinogens 0.1% or greater)

Component	CAS Number	OSHA PEL	ACGIH TLV	Density Lbs/in ³ & g/cm ³	% (optional)
Cadmium (Cd)	7440-43-9	.2 dust / .1 fume	.05 mg/m ³ (Dust&Fume)	.312 & 8.636	90 – 10%
Tin (Sn)	7440-31-5	2mg/m ³	2mg/m ³	.264 & 7.324	10 – 90%

No other hazardous material is present in concentrations greater than 1% (0.1% for Carcinogens)

NA = Not Applicable NE = Not Established NAIF = No Applicable Information found

SECTION IV: FIRST AID MEASURES

Ingestion: NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 2-8 oz. (60-240ml) of water. If vomiting occurs naturally, have victim rise mouth with water again. Immediately obtain medical attention and bring a copy of this SDS.

Skin Contact: *Dust:* Remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm gently flowing water and non-abrasive soap for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or else discard. *Molten Metal:* Flush contact area to solidify and cool, but do not attempt to remove encrusted material or clothing. Cover burns and seek medical attention immediately.

Inhalation: Remove source of contamination or move victim from exposure area to fresh air immediately. If breathing is difficult, trained personnel should administer medical oxygen. DO NOT allow victim to move around unnecessarily. Treat pulmonary edema as a priority, even if no symptoms (i.e. wheezing, coughing, shortness of breath, tec.) are apparent. Symptoms of pulmonary edema can be delayed up to 48 hours after exposure. Quickly transport victim to an emergency care facility.

Eye Contact: Do not allow victim to rub eye(s). Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, while holding eyelid(s) open. If irritation persists, immediately obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye. Immediately call a POISON CENTER or doctor/physician.

SECTION V: FIRE FIGHTING MEASURES

Flash point & Methods Used: N/A
 Auto Ignition Temperature: N/A
 Flammability Limits: (in air, % by volume) LEL: N/A and UEL: N/A
 Extinguisher Media: CO₂ or dry chemical extinguisher.

**DO NOT USE WATER ON MOLTEN METAL:
 LARGE FIRES MAY BE FLOODED WITH WATER FROM A DISTANCE**

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Cadmium-Tin Solders for Most Metals

SDS Number: 151

Page 3 of 4

Special Fire Fighting Procedures

Use NIOSH/MSHA -approved self-contained breathing apparatus and full protective clothing if involved in fire.

Unusual Fire and Explosion Hazards

Finely divided dust may form explosive mixture with air.

NEVER DROP WATER OR LIQUIDS INTO MOLTEN SOLDER.

***Do not plunge damp or wet solder bars/pieces into molten solder**

***Note: Alloys which contain Cadmium should never be heated to extremes beyond melting range**

SECTION VI: ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is spilled or released:

- Solder is solid / recyclable
- Vacuuming is recommended for accumulated metal dust from saw/grind operations.

SECTION VII: HANDLING AND STORAGE

Precautions to be taken in handling and storage:

- Dry storage; ambient temperature

Other Precaution / Special Handling:

Wet or moist ingot(s) WILL present an explosion hazard when submerged in molten solder.

***AVOID FIRE/EXPLOSION RISKS. Always preheat ingot before charging into furnace.**

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION



Respiratory Protection: Use NIOSH-approved breathing apparatus to prevent exposure to dusts and fumes.

Eye Protection: Approved safety glasses/welding goggles, appropriate to your procedure, should be worn.

Ventilation: Local Exhaust: YES; Mechanical: YES Special: Conform to your regulatory statutes.

Other: Standard protective equipment used in soldering (/applicable) operations.

*Protective gloves are recommended, especially for high temperature applications to prevent burns. *Conform to all local, state, federal regulations.

See also: 29 CFR 1910.132 - 29 CFR 1910.140. *Personal Protective Equipment*

29 CFR 1910.251 - 29 CFR 1910.257. *Welding, Cutting and Brazing*

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: NAIF

Melting Point: 176 to 316 °C / 350 to 600 °F

Vapor Pressure (mm Hg.): **CADMIUM ONLY: Health Significance ONLY >500 °C**

Vapor Density (AIR = 1): N/A

Density (50%Sn/50%Cd): .2880 lbs/cu in or 7.989 g/ml

Solubility in Water: 0 (solid)

Evaporation Rate (Butyl Acetate = 1): N/A

Appearance and Odor: Lustrous, silver metal; odorless / various shapes and sizes.

SECTION X: STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: None

Incompatibility (materials to avoid): Strong Acids, Strong Alkalis

Hazardous Decomposition Products: None; Hazardous Polymerization will not occur

SECTION XI: TOXICOLOGY INFORMATION

Cadmium (Cd): Fume produces metal fume fever which may result in severe tracheobronchitis, pneumonitis, pulmonary edema. Suspected acute inhalation exposure to Cadmium must be treated for pulmonary edema (throat dryness, cough, headache, vomiting, chest pains, and chills) by a physician. Delay until onset of puomony involvement may result in death. Cadmium is

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Cadmium-Tin Solders for Most Metals

SDS Number: 151

Page 4 of 4

transported via blood and stored in liver and kidneys. Can cause kidney damage. Chronic overexposure to Cadmium has been reported to cause an increased incidence of cancer of the prostate in men.

Tin (Sn): Elemental Tin is NOT generally considered to be toxic.

IT IS UNLIKELY THAT NORMAL EXPOSURE (USING APPROPRIATE PROTECTIVE EQUIPMENT) WOULD RESULT IN ILLNESS.

	*0 = Insignificant	1 = Slight	2 = Moderate	3 = High	4 = Extreme
	Health	Flammability	Reactivity	Special	
NFPA Rating	1	0	0	0	
HMIS Rating	1	0	0	0	

SECTION XII: ECOLOGY INFORMATION

This product will not biodegrade. It will oxidize if left out in the elements, but will not affect the surrounding ecology. General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Danger to drinking water if even extremely small quantities leak into the ground.

Results of PBT and vPvB assessment: PBT: Not applicable; vPvB: Not applicable.

SECTION XIII: DISPOSAL CONSIDERATION

Waste Disposal Method

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Disposal must be made according to official regulations. Dispose of according to federal, state, local, international, and OSHA regulations.

SECTION XIV: TRANSPORT INFORMATION

Ground - DOT Proper Shipping Name: Solder
Not regulated for transport by US DOT.

Air - IATA Proper Shipping Name: Solder
Not regulated for air transport by IATA.

SECTION XV: REGULATORY INFORMATION

SARA Title III Program: This product contains the following toxic chemicals subject to the reporting requirements of EPCRA of 1986 and 40 CFR 372

CHEMICAL NAME	CAS NO.	% / WEIGHT
Cadmium (Cd)	7440-43-9	90 – 10%

SECTION XVI: OTHER INFORMATION

This information must be included in all SDS that are copied and distributed for this material.

**GOOD HOUSEKEEPING PROCEDURES SHOULD BE MAINTAINED.
PERSONNEL SHOULD WASH THOROUGHLY BEFORE SMOKING OR EATING
FOOD AND DRINK SHOULD NOT BE CONSUMED, TOBACCO PRODUCTS USED, OR COSMETICS
APPLIED IN AREAS WHERE EXPOSURES EXIST.**

Please retain this sheet for your files. Kapp Alloy maintains a file of Safety Data Sheets (SDS) for each alloy produced in compliance with Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) & various right-to-know laws.

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Kapp Alloy and Wire, Inc. at the time of issue. It is our policy to include an MSDS with initial orders for each product. This submission is to become a matter of record and need not accompany subsequent shipments for the same product to the same customer. The information contained on this sheet is intended solely for employee health and safety education and not for contract specification purposes. No warranty, guarantee, or representation is made by Kapp Alloy and Wire, Inc., nor does Kapp Alloy and Wire, Inc. assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. Should you need additional information, contact us.