

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Golden Flux™ Paste for Aluminum Soldering 350–550°F / 177–288°C

SDS Number: 552 GHS

Page 1 of 4

SECTION I: PRODUCT AND COMPANY INFORMATION

Product Name: Kapp Golden Flux Paste for Aluminum Soldering 350–550°F / 177–288°C

CAS Numbers:

Component	CAS Number	Component	CAS Number
Aminoethylethanolamine	111-41-1	Ammonium Fluoborate	13826-83-0
Zinc Oxide	1314-13-2	Triethanolamine	102-71-6

Company Identification: Kapp Alloy and Wire, Inc., 1 Klein Street / PO Box 1188, Oil City, PA 16301 USA

Contact: Telephone: 814-676-0613 or 1-800-327-6533, Fax: 814-676-5565, Email: info@kappalloy.com**SECTION II: HAZARD INFORMATION****Classification of the mixture according to Regulation (EC) No. 1272/2008**

GHS05 Corrosion Eye Damage

H318 - Causes serious eye damage



GHS07 Skin Irritation

H302 – Harmful if swallowed.

H315 - Causes skin irritation.



GHS08 Health Hazard

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Label Elements according to Regulation (EC) No. 1272/2008

Hazard Pictograms:



GHS05



GHS07



GHS08

Signal Word: **DANGER**

Hazard-determining components of labelling:

Aminoethylethanolamine, Zinc Oxide, Ammonium Fluoborate, Triethanolamine

Hazard Statements:

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary Statements:

P220 - Wear protective gloves, clothing, eye, face, and respiratory protection.

P260 - Do not breathe dust/fumes.

P264 - Wash thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P305+P351+P338 – IF IN EYES: Flush with water for at least 15 minutes to remove irritant. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician immediately.

P304+P341 – IF INHALED: Terminate exposure and remove to fresh air. Call physician; advise of chemical composition (section III).

P302+P352 IF ON SKIN: Wash thoroughly with soap and water to remove any residue. If a rash develops, call a physician.

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Golden Flux™ Paste for Aluminum Soldering 350–550°F / 177–288°C

SDS Number: 552 GHS

Page 2 of 4

P301 + P310 IF SWALLOWED: Call a physician or Poison Control Center IMMEDIATELY; Advise of chemical composition. (Section III) and Potential Health Effects, (section VIII). Corrosive to mucous membranes. May contain corrosive hydrofluoric acid solution.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards:

PBT: Does not meet criteria for persistent – bio cumulative – toxic.

vPvB: Does not meet criteria for very persistent – very bio cumulative.

Target Organ Statement

- DANGER: CAUSES SEVERE BURNS TO SKIN, EYES, AND RESPIRATORY SYSTEM. HARMFUL IF INHALED, SWALLOWED, OR ABSORBED THROUGH SKIN.**

Effects of Chronic Exposure:

- Coughing, liver, and kidney effects; nausea, erythema. Osseous fluorosis due to fluoride.

SECTION III: COMPOSITION / INGREDIENTS

*(Hazardous components 1% or greater; Carcinogens 0.1% or greater). None of the materials in this product are listed in NTP, IARC, or OSHA as carcinogens.

COMPONENT	CAS NO.	SARA III	OSHA PEL	ACGIH TLV
Aminoethylethanolamine	111-41-1	-----	N/E	Hazard: Corrosive
Ammonium Fluoborate*	13826-83-0	< 20%	2.5 mg/m ³ as F*	2.5 mg/m ³ as F*
Zinc Oxide	1314-13-2	< 10%	5.0 mg/m ³	5.0 mg/m ³
Triethanolamine	102-71-6	-----	-----	5.0 mg/m ³

PEL = Permissible Exposure Limit; NA = Not Applicable; NE = Not Established; NAIF = No Applicable Information Found

***Ammonium Fluoborate:**

- The PEL for fluoride as F is 2.5 mg/m³. Chronic fluoride absorption can result in osseous fluorosis, increased radiographic density of the bones and mottling of the teeth. Read OSHA 29 CFR 1910.1000, July 1, 1980, standard for fluorides.
- The PEL for boron oxide is: 10 mg/m³, B₂O₃ as a fume. This compound when used as intended will generate fumes of boron oxide. Contact your industrial hygiene department.

SECTION IV: FIRST AID MEASURES

Ingestion: Call a physical or Poison Control Center IMMEDIATELY; Advise of chemical composition. (Section III) and Potential Health Effects, (section VIII). Corrosive to mucous membranes. May contain corrosive hydrofluoric acid solution.

Skin: Promptly flush with water to remove any residue. If a rash or burn develops, consult a physician. Product is corrosive. Hydrofluoric acid possible.

Inhalation: Terminate exposure and remove to fresh air. If fumes are inhaled, call physician immediately; over-inhalation may be harmful.

Eyes: Flush with water for at least 15 minutes to remove any residue. Get medical help NOW. Blindness can result. Hydrofluoric acid possible.

SECTION V: FIRE FIGHTING MEASURES

Flash point (°F): > 135°C / 275°F,

Flammability Limits: (in air, % by volume) LEL: 1.5, UEL: 10.0

Extinguisher Media: **Water, fog, foam, or dry chemical**

Special Fire Fighting Procedures Full protective equipment required. May release toxic ammonia, boron oxide, or fluoride fumes. Oxides of nitrogen.

Unusual Fire and Explosion Hazards Avoid splashing this material and solutions of it onto personnel. Hydrofluoric acid solution may be formed within water runoff. Decomposition may produce NO₂ fumes.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is spilled or released:

- Contain, absorb, sweep-up, and dispose. Flush area to chemical sewer.
- Prevent direct contact to skin, eyes, and clothes.
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Danger to drinking water if large quantities leak into the ground.

SECTION VII: HANDLING AND STORAGE

Precautions to be taken in handling and storage:

- Store flux in plastic container at 35-80°F (2-27°C), keep container tightly closed and away from foodstuffs.
- Wash hands thoroughly after handling to remove any residue.
- No eating or smoking in work area.

Other Precaution / Special Handling:

- Do not breathe fumes. Professionally wash contaminated clothing before re-use.
- Existing lung disorders will have increased toxic susceptibility.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear protective gloves of Nitrile Rubber or Natural Rubber to protect hands and wrists.

Respiratory Protection: Use NIOSH-approved breathing apparatus to prevent exposure to dusts and fumes.

Eye Protection: Chemical tight safety goggles, face shield. Do NOT wear contact lenses.

Ventilation: Maintain air flow away from user to remove all fumes and vapors, so that the PEL is never exceeded. Adhere to Environmental regulations for exhausts. Conform to applicable regulatory statutes.

Other: Full protective equipment normally used in soldering (/applicable) operations so as to prevent any contact. Review operations to avoid contact with hazardous gas, liquids or solids.

See also: 29 CFR 1910.132 - 29 CFR 1910.140. *Personal Protective Equipment*
29 CFR 1910.251 - 29 CFR 1910.257. *Welding, Cutting and Brazing*

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (@ 760 mmHg): N/A
 Solubility in Water (100 = complete): Freely Soluble 100
 Evaporation Rate (Butyl Acetate = 1): N/A
 Active Temperature Range: Active between 350–550°F / 177–288°C
 Percent volatiles by volume: N/A
 pH: 10-11
 Appearance and Odor: Amber paste with Ammonia odor
 Use: General purpose low temperature aluminum soldering flux, corrosive residue.

SECTION X: STABILITY AND REACTIVITY

Stability: Stable
 Conditions to avoid: Excessive heat; decomposes forming corrosive, skin penetrating, toxic gases
 Incompatibility (materials to avoid): Cyanides, sulfides, strong oxidants.
 Hazardous Combustion / Decomposition: Toxic hydrofluoric acid, ammonia, NO₂, and boron tri-fluoride gases.

SECTION XI: TOXICOLOGY INFORMATION

Swallowing: Can cause damage to digestive system. Corrosive to mucous membranes. May cause salivation, nausea, vomiting, diarrhea, and abdominal pain. Fluoride ion can reduce serum calcium levels, possibly causing fatal hypocalcaemia. Systemic toxicity and shock.

Skin Absorption / Contact: None currently known. Fumes may penetrate / absorb into skin.

Inhalation: Highly irritating to respiratory system. Coughing & sneezing. Existing lung disorders will be aggravated. Inhalation may yield: chills, labored breathing, fevers, and unproductive cough. The fluoride ion may cause hypocalcaemia – calcium deficiency in the blood. Inflammation and necrosis of mucous membranes.

Eye Contact: Strong irritation to eyes, tearing, burn of eye surface, corrosive to eyes. May cause blindness.

	0 = Insignificant	1 = Slight	2 = Moderate	3 = High	4 = Extreme
	Health	Flammability	Reactivity	Special	
NFPA Rating	2	1	1	0	
HMIS Rating	2	1	1	0	

SAFETY DATA SHEET

GHS SDS Date: 06/24/2017

SDS Name: Kapp Golden Flux™ Paste for Aluminum Soldering 350–550°F / 177–288°C

SDS Number: 552 GHS

Page 4 of 4

SECTION XII: ECOLOGY INFORMATION**STATE RIGHT-TO-KNOW PROGRAMS:****Pennsylvania:** The following chemicals are listed in PA code Title 34, Hazardous Substance List:
Aminoethylethanolamine, Ammonium Fluoborate, Zinc Oxide, Triethanolamine**California:** This material contains no compounds subject to the reporting and/or labeling requirements of Proposition 65.**SECTION XIII: DISPOSAL CONSIDERATION****Waste Disposal Method**

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Disposal must be made according to official regulations. Dispose of according to federal, state, local, international, and OSHA regulations.

SECTION XIV: TRANSPORT INFORMATION**DEPARTMENT OF TRANSPORTATION:** DOMESTIC GROUND
Proper shipping name: Corrosive Liquid, N.O.S.(Aminoethylethanolamine, Ammonium Fluoborate)
Hazard Class: 8
ID & Packing Group Number: UN 1760, PG II
ERG Guide Number: 154**SECTION XV: REGULATORY INFORMATION****TOXIC SUBSTANCE CONTROL ACT:** All components of this compound are listed within the TSCA inventory.**RoHS, REACH, and REACH-SVHC Compliance:**

This Product is RoHS and REACH Compliant. This product is free of REACH-SVHC substances.

SARA Title III Program:

This product contains the following toxic chemicals, subject to the reporting requirements of EPCRA of 1986 and 40 CFR 372.

CHEMICAL NAME	CAS NO.	CONCENTRATION
Zinc Compounds	7646-85-7	< 10%
Ammonium Fluoborate	13826-83-0	< 20%

*This information must be included in all SDS that are copied and distributed for this material.

CERCLA

The following components of the product and their respective RQs are listed in 40 CFR 302:

- Ammonium Fluoborate 13826-83-0 RQ = 5000 lbs.

SECTION XVI: OTHER INFORMATIONThis information must be included in all SDS that are copied and distributed for this material.

**GOOD HOUSEKEEPING PROCEDURES SHOULD BE MAINTAINED.
PERSONNEL SHOULD WASH THOROUGHLY BEFORE SMOKING OR EATING
FOOD AND DRINK SHOULD NOT BE CONSUMED, TOBACCO PRODUCTS USED, OR COSMETICS
APPLIED IN AREAS WHERE EXPOSURES EXIST.**

Please retain this sheet for your files. Kapp Alloy maintains a file of Safety Data Sheets (SDS) for each alloy produced in compliance with Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) & various right-to-know laws.

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Kapp Alloy and Wire, Inc. at the time of issue. It is our policy to include an SDS with initial orders for each product. This submission is to become a matter of record and need not accompany subsequent shipments for the same product to the same customer. The information contained on this sheet is intended solely for employee health and safety education and not for contract specification purposes. No warranty, guarantee, or representation is made by Kapp Alloy and Wire, Inc., nor does Kapp Alloy and Wire, Inc. assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. Should you need additional information, contact us.